

Turni-Q Linus



Single passage turnstile, in aluminum, passage width 800 mm

- Passage width 800 mm
- Simple and fast installation
- Long lifespan
- Operation and detection via contacts, IP or RS485 network
- Possibility of integration with SDK
- Spacious passageway for more comfort
- C5 lacquer protection (optional)
- Aluminium version > no corrosion



Type Operation	Single passage • Linus	
	Controlled	
Profiles frame and rotor	Painted aluminum	
Standard colour side panels and roof	RAL 7016	
Standard colour rotor and roof housing	RAL 9006	
Rotor	120°	
Weight approximate (kg)	190	
Number of mounting parts	5	
Integration by SDK	Yes	
Stainless steel mounting mold (option)	Yes	
Power supply	230 VAC (24 VDC possible)	
Consumption (standard version)	30 W	
Passage width	800 mm	
Operating temperature	-15°C up to +45°C	
IP protection class	IP 43	
Maximum throughput / minute	30 with free passage and 15 with controlled access	
MTBF	+ 1.000.000 (under normal maintenance)	
Warranty	2 years	

References	120°
Turni-Q Linus aluminum 800 mm	1-020101-0055-000-906-00
Option base	1-020101-0054-000-000-00
Option Large roof	1-020101-0055-010-906-00

